

# Zavdušňovací a odvzdušňovací ventily z materiálu PP



## Zavzdušňovací a odvzdušňovací ventil kuželový PP, typ S4

- Těsnění: EPDM
- Max. provozní tlak: d 16-d 75 PN10, d 90-d110 PN6

Ø	objímky Obj.č.	nátrubky Obj.č.	závit Obj.č.
DN10/d16-3/8"	12.1550	12.1568	12.1586
DN15/d20-1/2"	12.1552	12.1570	12.1588
DN20/d25-3/4"	12.1554	12.1572	12.1590
DN25/d32-1"	12.1556	12.1574	12.1592
DN32/d40-1 1/4"	12.1558	12.1576	12.1594
DN40/d50-1 1/2"	12.1560	12.1578	12.1596
DN50/d63-2"	12.1562	12.1580	12.2541
DN65/d75-2 1/2"	12.1564	12.1582	12.1600
DN80/d90-3"	12.1566	12.1584	12.1602
DN80/d110-4"	12.2539	12.2540	

- Těsnění: FPM
- Max. provozní tlak: d 16-d 75 PN10, d 90-d110 PN6

objímky Obj.č.	nátrubky Obj.č.	závit Obj.č.
12.1551	12.1569	12.1587
12.1553	12.1571	12.1589
12.1555	12.1573	12.1591
12.1557	12.1575	12.1593
12.1559	12.1577	12.1595
12.1561	12.1579	12.1597
12.1563	12.1581	12.1599
12.1565	12.1583	12.1601
12.1567	12.1585	12.1603
12.2542	12.2543	

---